



Product name	Wonder Yarn 26
Type	Tufted synthetic grass carpet
Material	PE Monofilament straight & PP Monofilament curled (UV Stabilized)
Yarn type	8,000 / 8 dTex PE monofilament straight & 5,000 / 8 dTex PP monofilament curled
Yarn quality	Environmental friendly, free of lead and cadmium
Primary backing	100% PP, black, U.V. stabilized, weight 172 gr/m2 (Double cloth with Fleece)
Secondary backing	Black Latex compound with a base of SBR, with drainage holes, 836 gr/m2
Water permeability	60 litre /min /100 cm <sup>2</sup>
Pile height	26 mm +/- 10%
Face weight	1,250 gr/m2 +/- 10%
Total weight	2,258 gr/m2 +/- 100 gr/m2
Tuft gauge	3/8 gauge
Stitches per 10cm linear	15 +/- 1
Stitches per m2	15,750 +/- 10%
Colour	Mix of light and dark green + caramel thatch
UV stability	Meets DIN 53387 Standard
Colour fastness	Xenon test: Bleu-scale >7 , Grey-scale > 4
Flammability	Tested to BS 4790 Standard
Critical Fall Heights (CFH)	Tested to EN 1177 - 1.2m (no underlay), 1.4m (with Lazypad 25mm Underlay), 2.4m (with Lazypad 50mm underlay)
Roll width	200 / 400 cm +/- 2 cm
Roll length	Standard 25 mtrs
Sand Infill	8kg's p/m2
Applications	Landscaping, Play, Multi

Evergreens UK have the right to alter each product specification in order to improve the product according to the newest technological applications. Evergreens UK is not legally liable in case of non-compliance with the above-mentioned specifications.



Product name	Wonder Yarn 36
Type	Tufted synthetic grass carpet
Material	PE Monofilament straight & PP Monofilament curled (UV Stabilized)
Yarn type	8,000 / 8 dTex PE monofilament straight & 5,000 / 8 dTex PP monofilament curled
Yarn quality	Environmental friendly, free of lead and cadmium
Primary backing	100% PP, black, U.V. stabilized, weight 172 gr/m2 (Double cloth with Fleece)
Secondary backing	Black Latex compound with a base of SBR, with drainage holes, 836 gr/m2
Water permeability	60 litre /min /100 cm <sup>2</sup>
Pile height	36 mm +/- 10%
Face weight	1,750 gr/m2 +/- 10%
Total weight	2,758 gr/m2 +/- 100 gr/m2
Tuft gauge	3/8 gauge
Stitches per 10cm linear	15 +/- 1
Stitches per m2	15,750 +/- 10%
Colour	Mix of light and dark green + caramel thatch
UV stability	Meets DIN 53387 Standard
Colour fastness	Xenon test: Bleu-scale >7 , Grey-scale > 4
Flammability	Tested to BS 4790 Standard
Critical Fall Heights (CFH)	Tested to EN 1177 - 1.1m (no underlay), 1.5m (with Lazypad 25mm Underlay), 2.4m (with Lazypad 50mm underlay)
Roll width	200 / 400 cm +/- 2 cm
Roll length	Standard 25 mtrs
Sand Infill	8kg's p/m2
Applications	Landscaping, Play, Multi

Evergreens UK have the right to alter each product specification in order to improve the product according to the newest technological applications. Evergreens UK is not legally liable in case of non-compliance with the above-mentioned specifications.